



MANNOL Compressor Oil ISO 46 2901

Specials highly-purified paraffin ashless mineral compressor oil with an extended replacement age. It ensures a stable and continuous operation of the equipment throughout the entire operation period.

Product properties:

- It contains antifriction, antiwear, anti-scuffing, anti-oxidising, anticorrosion and antifoaming additives;
- An excellent thermal stability;
- Great antiwear and anti-scuffing properties;
- An exceptional resistance to oxidisation and ageing;
- A minimal formation of deposits and sediments of all types: it guarantees the cleanliness of all mechanical parts, prevents the risk of fire or explosion;
- It has excellent anticorrosion, antiaerating and antifoaming properties and a low evaporation capacity;
- It is recommended for use at ambient temperatures of -30 °C and up;
- It has excellent cooling properties;
- It is compatible with all sealing materials;
- The replacement age is up to 2,000 running hours.

Use: This oil is mostly meant for air screw compressors with an oil injection system, operating on easy and moderate modes. It is suitable for air piston-type (easy, moderate operating modes) and air rotary (easy, moderate operating modes) compressors with the outlet air temperature up to 220 °C where the oil with ISO VG 46 viscosity is required.

It can be used in hydraulic systems as a low-ash oil and for the lubrication of a pneumatic tool.

In order to properly use it, thoroughly read the user's manual of the equipment.

Specifications

Approval

Recommendation

ISO Viscosity Grade 46

BROWN BOVERI HTGD 90117

ISO DP 6521 (L-DAA), 6521 (L-DAB), 6521 (L-DAG), 6521 (L-DAH)

DIN 51506 (VBL), 51506 (VCL), 51506 (VDL), 51515-1 (L-TD), 51515-2 (L-TG), 51517-2 (CL)

DIN 51524-1/-2

VDMA 24568

SIEMENS TLV 9013

MAG CINCINNATI P-38, P-55, P-54, P-57, P-62

BSI GB BS 489

GE GEK 32568 A, GEK 32568 C

CEGB 207001

US STEEL 120

MITSUBISHI E00-87182

MIL L 17672 D

PARKER DENISON HF-0

AFNOR FRANCE NF E 48-603

PACKAGING

1L	MN2901-1	Plastic	20 pcs/box
1000L	MN2901-IBC	Pallet tank	
208L	MN2901-DR	Drum	
60L	MN2901-60	Drum	
20L	MN2901-20	Plastic	
10L	MN2901-10	Plastic	