



MANNOL Hypoid 80W-90 GL-4/GL-5 LS 8106

A universal all-season mineral-based gear oil. It was developed for hypoid gears withstanding extreme loads; in heavy-duty bevel, cylindrical and worm pairs. It is recommended for use in differentials (including excessive friction – LS). It may be used for all types of manual transmissions, including the ones withstanding extremely heavy loads and high temperatures and in other transmission parts where extreme pressure and impact loads are encountered.

Product properties:

- The highest-quality unique base with optimal viscosity in a wide range of temperatures in combination with a latest-generation additive package in an elevated concentration ensures excellent antifriction properties thus ensuring a significant fuel economy;
- Due to its balanced composition, it ensures excellent antiwear and superior anti-scuffing properties that significantly extend the expected life of the technical equipment in all, even the most extreme, modes of operation in a wide range of ambient temperatures. The oil film has an enhanced resistance to increased pressures and temperatures;
- It prevents differentials from jamming and reduces piston wear. It ensures a reliable operation of self-locking differentials;
- It provides required low-temperature properties that ensure a sufficiently easy starting, reliable lubrication, as well as, when using the manual transmission, an easy and precise transmission shift at any ambient temperature (up to -30 °C) and in any operating conditions;
- It has an enhanced thermal-oxidative stability, resistance to the thermal degradation, ageing and viscosity stability that allows increasing the time between oil changes and reducing equipment maintenance costs;
- It decreases noise;
- It does not corrode non-ferrous metals;
- It is compatible with sealing materials, prevents them from swelling, hardening and shrinking that allows reducing the costs for spare parts.

It is recommended for use in manual transmissions of passenger cars and heavy-load manual transmissions of highway (freight trucks, buses, etc.), off-road (construction, mining, agricultural) and special vehicles produced by European, American and Asian manufacturers in which the required level of service characteristics is MIL-L 2105 D.

Comply with the manufacturer's instructions provided in the user's manual.

Specifications

SAE 80W-90

Approval

Recommendation

API MT-1

API GL-4/GL-5 LS (Limited Slip)

MIL L 2105 D

MACK GO-J

MAN 342

MAN 341 Type E2

MAN 341 Type Z2

ZF TE-ML 02B

ZF TE-ML 05A

ZF TE-ML 12L

ZF TE-ML 16B

ZF TE-ML 17B

ZF TE-ML 19B

ZF TE-ML 21A

SCANIA STO 1:0

DAIMLER DTFR 12B100

DAF

IVECO

VOLVO

PACKAGING

1L	MN8106-1	Plastic	20 pcs/box
1000L	MN8106-IBC	Pallet tank	
208L	MN8106-DR	Drum	
60L	MN8106-60	Drum	
20L	MN8106-20	Plastic	
10L	MN8106-10	Plastic	
4L	MN8106-4	Plastic	4 pcs/box