



ATF Exchanger (PNEU) CT4112

Product Features:

- Exclusive Deeptrans technology enhances fluid exchange performance by 50%.
- Patented Double Wall Tank design let new fluid become warm which gives protection to transmission and pipelines.
- The high precision scale marks allows more accurate result of calibration and transfer rate. Precise manual transfer rate is guaranteed, if necessary.
- One-button control to complete processes like new/waste fluid exchanging, - quick and convenient.
- Available to check real-time changing results via two sight glasses
- Vehicle database included and can be updated through USB port.
- Two fluid refill options
- Standard adapters work for most cars. Optional 72 types of adapter are available for special needs.
- Premium swivel casters with ideal-stop brake.

Technical data:

Voltage: AC 220 V 50/60 Hz 1Ph

Power - 140 W

Pressure gauge range 0~16 Bar (0~220 Psi)

Operating pressure ± 6 Bar (0~87 Psi)

Length of oil outlet hose - 2.5 m

Length of oil return hose - 2.5 m

Length of oil drain hose - 2.0 m

Filter element precision - 5 μ m

Volume of new oil tank ± 19.5 L

Volume of waste oil tank ± 15.5 L

Equivalent replacement error ± 0.05 L

Oil speed of oil exchange - 3.0 L/Min

Dimension of machine: 510 mm x 485 mm x 1360 mm

Package dimension: 495 mm x 495 mm x 1390 mm

Specifications

Approval

Recommendation