



MANNOL 4-Takt Power Plus 15W-50 7860

Innovative semi-synthetic ester-containing engine oil for 4-stroke high-loaded engines of motorbikes and pitbikes, motards etc. for off-road (enduro, motocross, trials etc.) and road (stunt riding, supermoto etc.) riding with extreme loads. Designed for reliable engine protection and gearbox durability.

Properties:

- A special additive package and synthetic components ensure a high coefficient of friction in the friction elements to avoid wear by preventing slippage and provide precise and smooth clutch operation when starting, accelerating and driving at a constant speed for easy gear changes;
- Thanks to its ester base it has good lubricating, anti-wear and anti-scuffing properties, reducing fuel consumption and increasing engine power as well as service life. It reliably protects the cylinder-piston group and valve train from wear;
- Created on a stable ester-containing part-synthetic base and designed for extreme operating conditions, it has good thermo-oxidative stability and resistance to high temperatures at which it retains an exceptionally strong oil film;
- Maintains stable viscosity characteristics under all operating conditions, including high shear rates. Ensures cold starts in winter;
- Special detergent-dispersing additives keep the engine separate parts perfectly clean;
- Possesses excellent anti-foaming properties and low evaporation;
- Highly effective inhibitors provide excellent anti-corrosion properties;
- Can be blended with similar synthetic oils;
- Compatible with all exhaust gas aftertreatment systems.

Designed for petrol 4-stroke engines of all types of motorbikes, ATVs, scooters and mopeds with air and liquid cooling, with integrated and non-integrated gearboxes, with oil bath clutch as well as “dry” clutch, and other motor vehicles with and without catalytic converters, meeting Euro V requirements where API SN or lower and JASO MA/MA2 performance level is required. Ideal for injector engines. Recommended for specific DUCATI engines requiring 15W-50 viscosity grade oil.

Observe the manufacturer's instructions in the engine manual, especially regarding oil change intervals!

Specifications

SAE 15W-50
API SN
JASO MA/MA2

Recommendation

DUCATI
HONDA
KAWASAKI
SUZUKI
YAMAHA
BMW

PACKAGING

	MN7860-1		
1L	MN7860-1	Plastic	20 pcs/box