

MANNOL[®] MATERIAL SAFETY DATA SHEET

Prepared according to Annex II of EC Regulation 1907/2006

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Getriebeoel-Additiv Automatik

Product Use: additive

Date of issue : 20.12.2012

Revision Date : 12.02.2013

Company Information: Sudheimer Car Technik Vertriebs GmbH

Address: Feldstrasse 154, 22880 Wedel, Germany

Information telephone : +49 (0) 4103 1211 118

Emergency telephone : +49 (0) 4103 1211 0

E-mail : info@sct-germany.de

Fax : +49 (0) 4103 1211 116

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Directive 67/548/EEC or 1999/45/EC

This product is not classified as dangerous, according to Directive 1999/45/EC or 67/548/EEC

2.2 Label elements

Directive 67/548/EEC or 1999/45/EC

Danger symbol and danger designation



Xn ; Harmful

S-phrases

35 This material and its container must be disposed of in a safe way.

37 Wear suitable gloves.

24 Avoid contact with skin.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P333/313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Special treatment see on this label.

P501 Dispose of contents and container to appropriate landfills or recycling facilities in accordance with local and national regulations..

2.3 Other hazards

None.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Hazardous components

ZINKALKYLDITHIOPHOSPHAT

Percentage : 15 %

Classification 67/548/EEC : Xi ; R36/38

Classification 1272/2008 (GHS) : Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319

For the wording of the listed risk phrases refer to section 16.

4 FIRST AID MEASURES

4.1 Description of first aid measures

Skin

Wash with soap and water. Get medical attention if irritation develops. Launder contaminated clothing before reuse.

Eyes

Flush with water at least 30 minutes. Get medical attention if eye irritation develops or persists.

Inhaled

Remove exposed person to fresh air if adverse effects are observed.

Swallowed

DO NOT INDUCE VOMITING. Get immediate medical attention.

Advice for first-aid providers

When providing first aid always protect yourself against exposure to chemicals or blood born diseases by wearing gloves, masks and eye protection. After providing first aid wash your exposed skin with soap and water.

4.2 Most important symptoms and effects, both acute and delayed

See section 11.

4.3 Indication of any immediate medical attention and special treatment needed

If exposed or concerned: Get medical attention.

5 FIRE FIGHTING MEASURES

5.1 Extinguishing Media

CO₂, dry chemical, or foam. Water can be used to cool and protect exposed material.

5.2 Special hazards arising from substance or mixture

See section 10 for additional information.

5.3 Advice for firefighters

Recommend wearing self-contained breathing apparatus. Water may cause splattering.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Personal protective equipment must be worn. Ventilate area if spilled in a confined space or other poorly ventilated area.

6.2 Environmental precautions

Prevent entry into sewers and waterways.

6.3 Methods and material for containment and cleaning up

Pick up free liquid for recycle and/or disposal. Residual liquid can be absorbed on inert material.

6.4 Reference to other sections

See sections 8 and 13 for additional information.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Keep containers closed when not in use. Wash thoroughly after handling. Launder contaminated clothing before reuse. Empty container contains product residue which may exhibit hazards of product. Dispose of packaging or containers in accordance with local, regional, national and international regulations.

Pumping Temperature

Ambient

Maximum Handling Temperature

70 °C, 158 °F

Maximum Loading Temperature

Not determined.

7.2 Conditions for safe storage, including any incompatibilities

See section 10 for incompatible materials.

Maximum Storage Temperature

Not determined.

7.3 Specific end use(s)

End uses are listed in an attached exposure scenario when one is required.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

8.1 Control parameters

none

8.2 Exposure controls

No particular measures required.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties Relevant safety data

Form:		Liquid
Colour :		red
Odour:		Oil. Fain
Boiling temperature / boiling range :	(1013 hPa)	>160°C
Flash point :		>100°C
Density :	(20 °C)	0,87 – 092 g/cm3
Viscosity :	(20 °C)	<10mPa.s
Solubility in water		Negligible

9.2 Other information

None.

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 - 10.6.

10.2 Chemical stability

Material is normally stable at moderately elevated temperatures and pressures.

10.3 Possibility of hazardous reactions

Will not occur.

10.4 Conditions to avoid

Not determined.

10.5 Incompatible materials

Oxidizing agents.

10.6 Hazardous decomposition products

Smoke, carbon monoxide, carbon dioxide, aldehydes and other products of incomplete combustion.

11. TOXICOLOGICAL INFORMATION

General: Low order of acute toxicity, but aspiration following ingestion and vomiting may cause severe and potentially fatal chemical pneumonitis. Does not absorb in acute toxic amounts through the skin. Exposure to high concentrations of oil mist may cause irritation to the respiratory organ. Exposure to the eye is slightly irritating, but does not injure eye tissue. Continuous or repeated skin contact combined with poor personal hygiene may cause dermatitis like eczema and oil acne. Used oil may contain harmful contaminants.

Skin contact: Product that under high pressure has been forced under the skin, may cause serious cell damage/death under the skin. Often or prolonged skin contact with used engine oils can cause cancer of the skin.

12. ECOLOGICAL INFORMATION

Mobility: Low solubility in water, floats on water.

Persistence/Degradability: Potentially degradable, but will persist in the environment for long periods.

Accumulation: Contain components with the potential to bioaccumulate. (logPow > 3)

Ecotoxicity: Not harmful to aquatic organisms. Expected LC/EC 50 value > 100 mg/l.

13. DISPOSAL CONSIDERATIONS

Disposal methods: Recover and reclaim or recycle, if practical. Do not allow runoff to sewer, waterway or ground. Confirm disposal procedures with environmental engineer and local regulations.

Contaminated packaging: Drums that are to be recycled must be thoroughly evacuated. Turn empty drum up side down, somewhat leaning (ca 10) with opening in lowest position. Let remaining products run out until drum is drip-free. Do not reseal without ventilating at a place free from ignition sources. See section 7 for further instructions.

Code of waste EWC: 13 02 05

Waste engine, gear and lubricating oils-mineral-based non-chlorinated engine, gear and lubricating oils.

Always check the given waste codes according to the actual conditions of manufacturing, formulation or use in your facilities.

14. TRANSPORT INFORMATION

14.1 UN number

The product does not constitute a hazardous substance in national / international road, rail, sea and air transport.

14.2 UN proper shipping name

The product does not constitute a hazardous substance in national / international road, rail, sea and air transport.

14.3 Transport hazard class(es)

The product does not constitute a hazardous substance in national / international road, rail, sea and air transport.

14.4 Packing group

The product does not constitute a hazardous substance in national / international road, rail, sea and air transport.

14.5 Environmental hazards

The product does not constitute a hazardous substance in national / international road, rail, sea and air transport.

14.6 Special precautions for user

None.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Water pollution classification

Class : 2 Classification according to VwVwS

15.2 Chemical safety assessment

There are no data available on the product itself.

16. OTHER INFORMATION

Further information

R-Phrases of components

36/38 Irritating to eyes and skin.

GHS Hazard statements of components

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Explanations of R-phrases in section 2:

Information Sources: The Classification and Labelling of Petroleum Substances to the EU Dangerous Substance Directive. Information from raw material suppliers.

Disclaimer: This information is based on our current knowledge and is intended to describe the product for the purpose of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of product. Receiver of our product is responsible for that applicable laws and regulations are being followed.