

Product Code:

# 7404

# SAFARI

## Universal engine oil

Meets the requirements:

SAE 20W-50

API SN/CH-4

Safari is a multigrade engine oil with highly purified mineral basis for highly accelerated gasoline and diesel engines with and without turbocharger, used in tough conditions. Contains low-ash additives to prolong the endurance of the catalyst. Has stable viscosity during the whole used period. Guarantees safe engine combustion at extreme loads.

### Product Characteristics:

Test	Method	Unit	Result
SAE-class			20W-50
Density at 15°C	D 1298	kg/m <sup>3</sup>	890
Viscosity at 40°C	D 445	CSt	168,64
Viscosity at 100°C	D 445	CSt	18,37
Viscosity at -15°C	D 5293	CP	8640
Viscosity index	D 2270		121
Pour point	D 97	°C	-33
Flash point	D 92	°C	240
TBN	D 2896	gKOH/kg	6,20

### Volume:

1L	MN7404-1	10L	MN7404-10
3L	MN7404-3	20L	MN7404-20
4L	MN7404-4	60L	MN7404-60
5L	MN7404-5	208L	MN7404-DR
7L	MN7404-7	1000L	MN7404-IBC



[www.mannol.de](http://www.mannol.de)

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, [info@sct-germany.de](mailto:info@sct-germany.de), tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

# MANNOL®